



Characteristics of the appliance

Master data

| | |
|------------------------------|--------------------------|
| Entry from | 04.11.2010 |
| Manufacturer | Oranier Heiztechnik GmbH |
| Model | WKK 722 |
| Product code | 7838 65 |
| Nominal heat output [kW] | 7 |
| Continuous burning appliance | — |
| Type test standard | DIN 18891 |
| Year of testing | 1998 |
| Test laboratory | RWE Rheinbraun AG |
| Number of test laboratory | 4.1 |
| Number of test report | RBW BF 1-Hn 12/98 |

Flue gas values

| | |
|-----------------------------|-------------|
| | Wood |
| Flue gas mass flow [g/s] | 9 |
| Flue gas temperature [°C] | 300 |
| Necessary flue draught [Pa] | 12 |

Further important characteristics of the appliance

| | |
|---|---|
| Suitability for installation to a shared flue ¹⁾ | |
| Connectivity to the central heating system | — |
| General technical approval for room sealed operation | — |

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system [please see installation manual].

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency for wood

Standard DIN EN 13240 [Intermittent burning]: Roomheater with flat-layer firing

Evaluation

| | | |
|---|---|------------------------|
| D - 1.BImSchV | ! | Details Explanation |
| FR - Crédit d'impôt à la transition énergétique | ! | Details |

According to the transitional rule §26 the appliance can be used until 31.12.2024.